decorator test later on, after you get this one passing. It walks through the interaction, conveniently touching a significant part of the Capybara API.

Let's go through the Capybara API, looking at the Capybara method calls you use in this test and then exploring related methods. Then we'll go through the rest of the process and make the test pass.

The Capybara API: Navigating

Capybara has one method to navigate to arbitrary routes in your system, and it's the first line of your test: visit(project_path(project)). The visit method takes one argument, which is a string URL (in this case, a Rails routing method that returns a string URL). The route generated by the visit method is always an HTTP GET. If you want to simulate a POST or any other kind of HTTP method, the recommended mechanism in Capybara is to navigate to a link or form button on the web page that triggers the desired interaction.

The Capybara API: Interacting

After the test hits the project_path URL, you start to use Capybara methods to interact with the elements on the page. Specifically, you use the fill_in method to place text in a text field, then the select method to choose an option from a select menu, and finally the click_on method to click on a button and submit a form.

Capybara is quite flexible in how it allows you to specify the element you want to work with. You can specify any element by its DOM ID. Form elements can also be specified by their name attribute. Form elements that have attached label tags can be specified by the attached label's text. Elements like HTML anchor tags that have internal text can be specified via that text. An HTML anchor tag whose body is an image can be located by the image's alt text attribute.

In other words, if you have an HTML snippet like this:

```
<form>
  <label for="user_email">Email</label>
  <input name="user[email]" id="user_email" />
</form>
```

You can use Capybara to access that form element with any of the following:

```
fill_in("user_email", with: "noel@noelrappin.com")
fill_in("user[email]", with: "noel@noelrappin.com")
fill_in("Email", with: "noel@noelrappin.com")
```