and support, and a features/support/env.rb file (the latter is analogous to spec_helper.rb). Also, it modifies the database.yml file to add a cucumber environment that copies the test environment. Cucumber has some additional configuration options; you can type rails generate cucumber:install —help to see them.

Writing Cucumber Features

In Cucumber you write tests as a series of steps using a minimal language called Gherkin. An individual Cucumber test is called a Scenario, and a group of them is called a Feature.

Let's take the Capybara integration test from the last section and convert it to Cucumber. Cucumber feature files go in the features directory and typically end in .feature. Here is features_add_task.feature:

integration/03/features/add_task.feature

```
Feature: Adding a task

  Background:
    Given a project

  Scenario: I can add and change the priority of a new task
    When I visit the project page
    And I complete the new task form
    Then I am back on the project page
    And I see the new task is last in the list
    When I click to move the new task up
    Then I am back on the project page
    And the new task is in the middle of the list
```

This file has three parts. The Feature declaration is at the top. Your Cucumber file needs to have one, but the description there is strictly for the humans; you can put anything there that you want. Gherkin is whitespace-sensitive, so anything that goes beyond that top line needs to be indented.

The next section is the Background, which is optional. It might not be clear from the preceding code, but the Background line is indented subordinate to Feature. In Cucumber, Background is like Minitest's setup and RSpec's before, indicating code that is run to initialize each test. In your case, since you have only one Scenario, it's not necessary to have a Background. But if you did have multiple "Add a task" scenarios, they'd likely all share that one common Background.

After the Background comes the Scenario, which is the actual test. Both Background and Scenario are made up of steps. In Cucumber a step usually consists of Given, When, or Then, followed by a sentence. This corresponds to the same basic structure I've been using informally to discuss tests throughout the book: Given indicates a precondition to the action. When indicates a user action that