changes the state of the application. Then specifies the result of the state change. You can also start a line with And or But (or *, if you must) if it's desirable for readability. Using And or But to start a line means that the line belongs to whichever of Given/When/Then is closest above it.

The distinction between Given, When, and Then is for us humans. Cucumber does not require the steps to be in a particular order. As you'll see, each Cucumber step is matched to code to determine its behavior. When it comes time to make that match, the Given/When/Then type of the header is not significant in the match.

This scenario is executable now, using the cucumber command, or you can specify the file with cucumber feature/add_task.feature. The output comes in two parts. The first is a listing of the execution step by step, which starts like this:

```
Background:       # features/add_task.feature:3
    Given a project # features/add_task.feature:4
      Undefined step: "a project" (Cucumber::Undefined)
      features/add_task.feature:4:in `Given a project'

  Scenario: I can add and change priority of a new task
                  # features/add_task.feature:6
    When I visit the project page
                  # features/add_task.feature:7
      Undefined step: "I visit the project page" (Cucumber::Undefined)
      features/add_task.feature:7:in `When I visit the project page'
```

You can't see this on the page, but all that text other than the Background and Scenario lines will be yellow.

When a scenario is run, Cucumber attempts to run each step by matching it to a step definition and executing that step definition. In this output Cucumber helpfully tells you the line number of each step it tries to execute, and then tells you that the step is undefined. That makes sense because you haven't defined any steps yet.

After it goes through all the steps and reports that you have one scenario with eight steps, of which one scenario and eight steps are undefined, Cucumber adds some extra output to the terminal. It starts like this:

```
You can implement step definitions for undefined steps with these snippets:

Given(/^a project$/) do
  pending # express the regexp above with the code you wish you had
end

When(/^I visit the project page$/) do
  pending # express the regexp above with the code you wish you had
end
```