reorder still holds. The old test assumed the entire page was redrawn. The new test moves the same DOM ID around without redrawing the whole page. This means the DOM ID of the row you care about no longer changes, so you need different acceptance criteria. Now you're using the nth-child selector to pick the second .name child of tbody.

I also added a metadata value :js to the reorder task. Right now that metadata tag does nothing. The test passes without the :js tag. (Trust me; I'll come back to that in a moment.)

To make sure the JavaScript client handles the reorder functionality, you need to detach the existing up and down links from sending requests back to the server. In exchange, you'll give those link elements DOM classes and attributes (such as data-task-id) that you'll use in the resulting JavaScript:

js_integration/01/app/views/projects/show.html.erb

```
<h2>Project <%= @project.name %></h2>

<h3>Existing Tasks:</h3>

<table>
  <thead>
    <tr>Name</tr>
    <tr>Size</tr>
  </thead>
  <tbody>
    <% @project.tasks.each do |task| %>
      <tr id="task_<%= task.project_order %>" data-task-id=<%= task.id %>>
        <td class="name"><%= task.title %></td>
        <td class="size"><%= task.size %></td>
        <td class="completed"><%= task.completed_at %></td>
        <td>
          <button class="up-button">Up</button>
          <button class="down-button">Down</button>
        </td>
      </tr>
    <% end %>
  </tbody>
</table>

<h3>New Task</h3>

<%= form_for Task.new(project_id: @project.id) do |f| %>
  <%= f.hidden_field :project_id %>
  <%= f.label :title, "Task" %>
  <%= f.text_field :title %>
  <%= f.label :size %>
  <%= f.select :size, [1, 2, 3, 4, 5] %>
  <%= f.submit "Add Task" %>
<% end %>
```