js_integration/01/app/views/layouts/application.html.erb

```
<!DOCTYPE html>
<html>
  <head>
    <title>Gatherer</title>
    <%= csrf_meta_tags %>

    <%= stylesheet_link_tag    'application', media: 'all', 'data-turbolinks-track':
       'reload' %>
    <%= javascript_include_tag 'application', 'data-turbolinks-track': 'reload' %>
    <%= javascript_pack_tag "projects" %>
  </head>

  <body>
    <%= yield %>
  </body>
</html>
```

That javascript_pack_tag helper is the new Webpacker equivalent of javascript_include_tag. It similarly causes the Webpack build from the given file (in this case projects.js) to be included at the point of the helper.

With all this included, the Capybara JavaScript test now passes. You may see some output in the test run that says Webpack is compiling the JavaScript for inclusions.

Webpack in Developer Mode

Like the Rails asset pipeline, Webpack converts the files under its domain into JavaScript and CSS that the browser can handle. Unlike the Rails asset pipeline, it uses its own process to monitor the files for changes and to recompile them. As of Webpacker 3.0 that process, webpack-dev-server, runs inline with the Rails development server by default. However, you can separate them if you'd like. Running webpack-dev-server separately allows the compile to happen when the file changes rather than when you hit the page, which can feel faster. Also, when run standalone, webpack-dev-server can give you live reload while editing.

You can use a tool called Foreman to easily run that process alongside your Rails server.[5]

First, add Foreman to the Gemfile:

```
gem "foreman"
```

Follow that with a bundle install.

5. http://ddollar.github.io/foreman