- frameworks specifies the test frameworks being used—in this case that means Jasmine.
- files identifies the file pattern Karma will match against when looking for test files. So, in this case, any file in spec/javascripts that ends with _spec.js is a test file.
- preprocessors tells Karma to use Webpack and source maps to process each file.
- reporters tells Karma to run output through the mocha reporter.
- browsers identifies the browser that will run all the tests when Karma is invoked. In this case, you're using headless Chrome.
- singleRun tells Karma to run once when invoked, then stop. Otherwise, it will stay open and autorun when a test file changes. I find autorun kind of irritating these days, so I don't use it.
- webpack denotes your Webpack configuration. You're just loading in the one you've already defined.

First, you need to make some tweaks to the Webpack configuration. The test environment needs to change slightly to look like this:

js_jasmine/01/config/webpack/test.js

```
const environment = require("./environment")
environment.plugins.get("Manifest").opts.writeToFileEmit = process.env.NODE_ENV
         !== "test"
const config = environment.toWebpackConfig()
config.devtool = "inline-source-map"
module.exports = config
```

The change is the env.NODE_ENV !== "test" value for writeToFileEmit. You don't want this manifest file to be written in the test environment, as you don't need it to be served, and it can interact badly with Karma. You're also adding some lines to have Webpack generate source maps.

Finally, I want to add a script section to the project.json file:

js_jasmine/01/package.json

```
{
  "scripts": {
    "test": "NODE_ENV=test karma start"
  },
  "dependencies": {
    "@rails/webpacker": "^3.2.1",
    "jquery": "^3.3.1"
  },
```