```
  it("can identify the last element of a project", () => {
    expect(project.lastTask().name).toEqual("End Project")
    expect(project.lastTask().isLast()).toBeTruthy()
    expect(project.lastTask().isFirst()).toBeFalsy()
    expect(project.lastTask().index).toEqual(2)
  })

  it("can move a task up", () => {
    project.tasks[1].moveUp()
    expect(project.firstTask().name).toEqual("Middle Project")
    expect(project.tasks[1].name).toEqual("Start Project")
    expect(project.lastTask().name).toEqual("End Project")
  })

  it("can move a task down", () => {
    project.tasks[1].moveDown()
    expect(project.firstTask().name).toEqual("Start Project")
    expect(project.tasks[1].name).toEqual("End Project")
    expect(project.lastTask().name).toEqual("Middle Project")
  })

  it("handles asking for the top task to move up", () => {
    project.firstTask().moveUp()
    expect(project.firstTask().name).toEqual("Start Project")
    expect(project.tasks[1].name).toEqual("Middle Project")
    expect(project.lastTask().name).toEqual("End Project")
  })

  it("handles asking for the bottom task to move up", () => {
    project.lastTask().moveDown()
    expect(project.firstTask().name).toEqual("Start Project")
    expect(project.tasks[1].name).toEqual("Middle Project")
    expect(project.lastTask().name).toEqual("End Project")
  })
})
```

The test file starts by importing Test and Project from the file where they live. Note that the file name is specified relative to the test file, not relative to the project root. This is using ES6 module syntax; you'll see the export half of this when we look at the passing code.

The rest of the code looks similar to RSpec that was modified to use JavaScript functions rather than Ruby blocks. You start with a describe call that takes a string argument and a function. Inside that function you declare a variable, project. The variable needs to be declared outside the beforeEach and it functions so that it is visible to both of them. You have beforeEach, which takes a function as an argument, and executes that function before each spec runs. You also have it, which takes a name and a function and executes the actual spec. Inside the it you have a similar set of matchers using expect and then a series of matcher functions that are described in *Jasmine Matchers*, on page 201.