```
    this.project.swapTasksAt(this.index - 1, this.index)
  }

  moveDown() {
    if (this.isLast()) {
      return
    }
    this.project.swapTasksAt(this.index, this.index + 1)
  }
}
```

Jasmine Matchers

So far you've only seen toEqual as a core Jasmine matcher, but Jasmine defines quite a few. Here are the built-in matchers.

Matcher	Passes if
toBe(actual)	expected === actual (JavaScript triple equal).
toBeCloseTo(actual, precision)	The floating-point value of actual is within precision amount of the expected value.
toBeGreaterThan(actual)	expected > actual.
toBeFalsy()	The expected value is a JavaScript falsy value.
toBeLessThan(actual)	expected < actual.
toBeNull()	The expected value is null.
toBeTruthy()	The expected value is a JavaScript truthy value.
toBeUndefined()	The expected value is undefined; no actual argument needed.
toContain(actual)	expected is an array that contains the actual value.
toEqual(actual)	expected and actual are equal values. Exactly what that means depends on their type. toEqual is based on a (no kidding) 120-line method in Jasmine that uses slightly different criteria for each built-in type and does a deep property comparison of JavaScript objects. Long story short, it tends to do what you'd expect.
toMatch(actual)	expected is a string that matches the actual regular expression.
toThrow()	expected is a function that throws an exception when called.

Any matcher can be negated by chaining not before the matcher, as in expect(1 + 1).not.toEqual(3).