In testdouble.js, you add behavior with the when method, and the API to it is a little unusual. Here's a basic usage:

```
const fake = td.object["remoteInit"]
td.when(fake.remoteInit(1)).thenReturn(7)
```

There are two parts to this when invocation: the call to when itself, and then the chained method afterward that defines the behavior.

The argument to when is meant to be the entire call to the test double, potentially with arguments specified. It's a demonstration of the call that the test expects to be made by the code under test.

In this case, you expect the test to make the call fake.remoteInit(1) to cause the test double to return the value 7. If you make the call fake.remoteInit(2)—changing the argument—the specified behavior is not triggered and the result of that call is undefined.

This interface to creating test-double behavior has the huge advantage of making the most common action—returning a value when a function is called—very simple. The library does get more complicated from there.

First, if you want to access an instance method of a test double created with td.constructor, the nature of JavaScript objects requires you to invoke that method via the prototype object, as in td.when(FakeLoader.prototype.load()). As in RSpec, you can pass in argument matchers in place of literal arguments if you want the test double to match against a wider array of behavior. (You can see the full list of stubbing behavior online.[10]) Here are some of the most useful ones:

- anything, as in td.when(fake.remoteInit(anything())), which matches, well … anything. You do have to match the number of arguments, so in this case fake.remoteInit(12) matches, but fake.remoteInit(12, 13) does not.
- contains(<something>) matches if the argument to the eventual test double is contained by the argument to contains. The argument can be a string, a regular expression, an array, or an object.
- isA() matches based on type: td.when(fake.remoteInit(isA(Number))). This works for built-in types, ES6 classes, or older-style objects that define constructors.
- not() matches if a particular value doesn't match, as in td.when(fake.remoteInit(not(12))).

10. https://github.com/testdouble/testdouble.js/blob/master/docs/5-stubbing-results.md