```
  loadFromData(data) {
    this.name = data.project.name
    data.project.tasks.forEach(taskData => {
      this.appendTask(new Task(
        taskData.title, taskData.size, taskData.project_order))
    })
    return this
  }

  appendTask(task) {
    this.tasks.push(task)
    task.project = this
  }

  firstTask() {
    return this.tasks[0]
  }

  lastTask() {
    return this.tasks[this.tasks.length - 1]
  }

  swapTasksAt(index1, index2) {
    const temp = this.tasks[index1]
    this.tasks[index1] = this.tasks[index2]
    this.tasks[index2] = temp
    new ProjectTable(this, ".task-table").insert()
  }
}
```

js_jasmine/02/app/javascript/packs/project_loader.js

```
export class ProjectLoader {
  constructor(project) {
    this.project = project
  }

  load() {
    return $.ajax(this.ajaxData())
  }

  ajaxData() {
    return {
      url: `/projects/${this.project.id}.js`,
      dataType: "json"
    }
  }
}
```

ProjectLoader is a simple class that takes in a Project and makes an Ajax call, which returns a promise. The test double version of that call automatically resolves the promise. When Project#load calls ProjectLoader#load, it looks at that promise, and when it resolves it passes the data to loadFromData—the code is then(data => this.loadFromData(data)). The test double version resolves the promise