minitest/01/test/models/task_test.rb

```
Line 1  require "test_helper"
-
-   class TaskTest < ActiveSupport::TestCase
-     test "a completed task is complete" do
5       task = Task.new
-       refute(task.complete?)
-       task.mark_completed
-       assert(task.complete?)
-     end
10
-     test "an uncompleted task does not count toward velocity" do
-       task = Task.new(size: 3)
-       refute(task.part_of_velocity?)
-       assert_equal(0, task.points_toward_velocity)
15    end
-
-     test "a task completed long ago does not count toward velocity" do
-       task = Task.new(size: 3)
-       task.mark_completed(6.months.ago)
20      refute(task.part_of_velocity?)
-       assert_equal(0, task.points_toward_velocity)
-     end
-
-     test "a task completed recently counts toward velocity" do
25      task = Task.new(size: 3)
-       task.mark_completed(1.day.ago)
-       assert(task.part_of_velocity?)
-       assert_equal(3, task.points_toward_velocity)
-     end
30  end
```

This looks broadly similar to the RSpec you've been looking at, but the syntax has some clear differences. Let's take a look at the main ones.

On line 1 the file test_helper is required; it contains Rails and application-related setup common to all Minitest files. It's the file to which you just added Mocha.

In Minitest you can't put a test method just anywhere or name it just anything; tests need to be methods of a subclass of the class Minitest::Test. (The class ActiveSupport::TestCase that the test uses is, in fact, a subclass of Minitest::Test.) In standard Minitest, a test method is any method whose name starts with test_, as in test_this_thing_with_a_long_name. However, this test uses a Rails ActiveSupport extension that allows you to just say test "some string", followed by a block. Rails uses metaprogramming to convert test "some string" into a method called test_some_string, which invokes the block and is, by virtue of the name, executed by Minitest during a test run. I find the test_long_name syntax to be significantly less readable, so let's use the shortcut here.