## Minitest Helper Tests

Rails provides the ActionView::TestCase class, which is a subclass of ActiveSupport::TestCase designed to load enough of the Rails controller structure to enable helpers to be called and tested. Let's look at the Minitest version of the name_with_status helper tests:

minitest/02/test/helpers/project_helper_test.rb

```
require "test_helper"
class ProjectsHelperTest < ActionView::TestCase
  test "project name with status info" do
    project = Project.new(name: "Project Runway")
    project.stubs(:on_schedule?).returns(true)
    actual = name_with_status(project)
    expected = "<span class='on_schedule'>Project Runway</span>"
    assert_dom_equal(expected, actual)
  end

  test "project name with status info behind schedule" do
    project = Project.new(name: "Project Runway")
    project.stubs(:on_schedule?).returns(false)
    actual = name_with_status(project)
    expected = "<span class='behind_schedule'>Project Runway</span>"
    assert_dom_equal(expected, actual)
  end

  test "project name using assert_select" do
    project = Project.new(name: "Project Runway")
    project.stubs(:on_schedule?).returns(false)
    assert_select_string(name_with_status(project), "span.behind_schedule")
  end
end
```

The assert_dom_equal method doesn't have an RSpec equivalent. You use assert_dom_equal to compare the string you expect to the string you get from the helper. The assert_dom_equal assertion checks that two strings both resolve to equivalent DOM structures; it tests that attributes have identical values but don't necessarily need to be in the same order. It's nice to have because it spares you having to do some fiddling with HTML strings in your test.

There's another assert_select trick I wanted to mention—the ability to pass a block to assert_select and then have assert_select work on an arbitrary HTML element rather than the entire page output.

If you pass a block to assert_select, then asset_select invokes the block with a single argument containing an array of all HTML elements that match your selector. You can then do whatever you want with that array. One choice is to iterate over the array and run further assertions, perhaps using assert_select.