The rspec-rails gem depends on the rspec gem proper. The rspec gem is mostly a list of other dependencies where the real work gets done, including rspec-core, rspec-expectations, and rspec-mocks. Sometimes rspec and rspec-rails are updated separately; you might choose to explicitly specify both versions in the Gemfile. Here we're putting rspec in the development group as well as in the test group so that you can call rspec from the command line, where development mode is the default. (RSpec switches to the test environment as it initializes.)

Install with bundle install. Then you need to generate some installation files using the rspec:install generator:

```
$ bundle install
$ rails generate rspec:install
      create  .rspec
      create  spec
      create  spec/spec_helper.rb
      create  spec/rails_helper.rb
```

What's a Spec?

What do you call the things you write in an RSpec file? If you're used to TDD and Minitest, the temptation to call them tests can be overwhelming. However, as I've discussed, the BDD planning behind RSpec suggests it's better not to think of your RSpec code as tests, which are things that happen after the fact. So, what are they?

The RSpec docs and code refer to the elements of RSpec as "examples." The term I hear most often is simply "spec," short for "specification," as in "I need to write some specs for that feature." I've tried to use "spec" and "example" rather than "test" in this book, but I suspect I'll slip up somewhere.

This generator creates the following:

- The .rspec file, where RSpec run options go. In RSpec 3.6 the default currently sets --require spec_helper, which ensures that the spec_helper file is always required.
- The spec directory, which is where your specs go. RSpec does not automatically create subdirectories like controller and model on installation. You can create the subdirectories manually or Rails generators will create them as needed.
- The spec_helper.rb and rails_helper.rb files, which contain setup information. The spec_helper.rb file contains general RSpec settings while the rails_helper.rb file, which requires spec_helper, loads the Rails environment and contains settings that depend on Rails. The idea behind having two files is to make