using RSpec, so the spec goes in the spec directory using a file name that is parallel to the application code in the app directory. We think this is a test of a project model, which would be in app/models/project.rb, so put the spec in spec/models/project_spec.rb. We're making very small design decisions here, and so far these decisions are consistent with Rails conventions.

Here's your spec of a project's initial state:

basics/01/spec/models/project_spec.rb

```
Line 1  require "rails_helper"
    2
    3  RSpec.describe Project do
    4    it "considers a project with no tasks to be done" do
    5      project = Project.new
    6      expect(project.done?).to be_truthy
    7    end
    8
    9  end
```

Let's talk about this spec at two levels: the logistics of the code in RSpec and what this test is doing for you in your TDD process.

Compared to other testing libraries, RSpec shifts the tone from an "assertion," potentially implying already-implemented behavior, to an "expectation," implying future behavior. The RSpec version, arguably, is easier to read than the Minitest version (though some strenuously dispute this). Later in this chapter I'll cover some other tricks RSpec uses to make expectations read like natural language.

The project_spec.rb file uses four basic RSpec and Rails features:

- It requires rails_helper.
- It defines a test suite with RSpec.describe.
- It creates an RSpec example with it.
- It specifies a particular state with expect.

On the first line, the file rails_helper, which contains Rails-related setup common to all tests, is required. (You'll peek into that file in the next chapter, when I talk about more Rails-specific test features.) The rails_helper file, in turn, requires a file named spec_helper, which contains non-Rails RSpec setup.

The RSpec.describe method is used on line 3. In RSpec, the describe method defines a suite of specs that can share a common setup. The first argument to describe is either a class name or a string. The first argument documents what the test suite is supposed to cover. You can then pass an optional number of metadata arguments, of which there are none at the moment. The metadata