With that bit of setup out of the way, you can write an integration test. In this case, you'll integrate your code with Twitter:

external/01/spec/system/shows_twitter_avatar_spec.rb

```
require "rails_helper"

RSpec.describe "task display" do

  let(:project) { create(:project, name: "Project Bluebook") }
  let(:user) { create(:user, twitter_handle: "noelrap") }
  let!(:task) { create(:task, project: project, user: user,
                              completed_at: 1.hour.ago, project_order: 1) }

  before(:example) do
    project.roles.create(user: user)
    sign_in(user)
  end

  it "shows a gravatar", :vcr do
    visit project_path(project)
    url = "http://pbs.twimg.com/profile_images/40008602/head_shot_bigger.jpg"
    within("#task_1") do
      expect(page).to have_selector(".completed", text: user.email)
      expect(page).to have_selector("img[src='#{url}']")
    end
  end

end
```

With one exception, this test is a simplified version of the integration test you wrote in Chapter 8, *Integration Testing with Capybara and Cucumber*, on page 151. The *given* here is the project, user, and task along with a simulated login. The *when* is visiting the show page for the project, and *then* you validate that the user associated with the task is displayed by both the user's email and Twitter avatar. I've seeded this test with a known Twitter avatar—mine—by setting the user's Twitter handle and then setting the expected image source to my known Twitter-profile URL.

You've probably noticed that the test has an unusual piece of metadata: :vcr. Since I've mentioned VCR a couple of times in this chapter you may have further assumed that, in this context, VCR has more to do with external service testing than it does with that Blockbuster store that closed 10 years ago.

Introducing VCR

VCR is one of my favorite testing tools. The concept is simple. When VCR is enabled, it intercepts any third-party HTTP request. By default, the first time the request is made, VCR allows the request to proceed normally. However, VCR saves the response and associated metadata to a YAML file, which VCR