This test has no dependency on the client, which is shown passing in a double rather than an actual User instance. Using a VCR cassette, you create a new adapter and assert that the adapter provides the expected URL when queried. The test also doesn't have a particular dependency on the Twitter gem, beyond the specific URL value being from Twitter's asset storage. This is a test of the adapter's behavior, not of the implementation.

The passing code requires a bit of Twitter connection setup:

external/02/app/models/avatar_adapter.rb

```
class AvatarAdapter
  attr_accessor :user

  def initialize(user)
    @user = user
  end

  def client
    @client ||= begin
      Twitter::REST::Client.new(
        consumer_key: Rails.application.secrets.twitter_api_key,
        consumer_secret: Rails.application.secrets.twitter_api_secret)
    end
  end

  def image_url
    client.user(user.twitter_handle).profile_image_uri(:bigger).to_s
  end
end
```

The Twitter gem requires a client to be created using the API keys you put in the secrets.yml file. The adapter lazily creates that client as needed.

Once the client is created, it calls the user method on the client with the Twitter handle and then grabs the profile_image_uri property. The gem uses the :bigger argument to determine the size of the resulting image, and you need to call to_s, because the actual property is an internal class of the Twitter gem and all you want is the URL. All of these are features of the interaction with the Twitter API that the rest of the application doesn't need to care about because the adapter is managing that information.

At this point, the adapter test passes. Even better, all the parts of the interaction have now been written and connected, so the integration test passes as well.

If you go to the spec/vcr directory, you now see two cassette files, one for each test. They are both about 150 lines long, so I'm not putting them in the book. The first few lines look like this: