Option	Description
:all	Always connects to HTTP and re-records. Useful for forcing cassette updates.
:new_episodes	Replays a request that is already on the cassette. New requests are made via HTTP and added to the cassette.
:none	Only replays existing cassettes; never makes an actual request.
:once	Replays existing cassettes; records new requests if the cassette doesn't exist. Raises an error on new requests if it does.

If you want to specify the recording options for all cassettes at once, you can do so in the configuration with the default_cassette_options method:

```
VCR.configure do |c|
  # existing configuration
  c.default_cassette_options = { record: :all }
end
```

By occasionally adding the previous line to the configuration for one test run, you get one run of smoke tests as all the VCR cassettes go back to their servers for data.

Let's look at a couple of other important configuration options.

Sometimes you want VCR to not deal with specific requests. The c.ignore_localhost = true property handles one common case, where you don't want VCR to touch requests back to the actual application being tested, such as Ajax requests or callbacks for authentication information. The method c.ignore_hosts takes an optional list of hostnames to ignore, and the method ignore_request {|req| CODE} ignores any request for which the associated block returns true.

By default, VCR looks for an exact match on the URI being requested when attempting to match a cassette request to a new HTTP request from the code, including query strings and HTTP methods. However, some services never have the exact same URI twice. For example, the Amazon API calls contain a timestamp. In other cases, additional headers may be relevant to how the request is processed. VCR provides the match_requests_on configuration option to manage the matching between cassette and request.

You use match_requests_on as an option to a VCR call or as a default. The argument is an array of elements that you want to use in the match. Valid values are :method, :uri, :host, :path, :query, :body, :headers, and :body_as_json. You can also use the method uri_without_params as a substitute for uri where there are parameters in the query string that are not important for the match.