To set up Guard, add the Guard gem and any of the dependent libraries to the Gemfile. Note that these all go in the development group, not the test group:

```
group :development do
  gem 'guard'
  gem 'guard-minitest'
  gem 'guard-rspec'
  gem 'guard-cucumber'
  gem "guard-jasmine"
  gem "rb-readline"
end
```

Then, from the command line, run the following:

```
$ guard init
guard init
20:17:50 - INFO - Writing new Guardfile to <FILE>
20:17:51 - INFO - cucumber guard added to Guardfile, feel free to edit it
20:17:51 - INFO - jasmine guard added to Guardfile, feel free to edit it
20:17:52 - INFO - minitest guard added to Guardfile, feel free to edit it
20:17:52 - INFO - rspec guard added to Guardfile, feel free to edit it
20:17:52 - INFO - teaspoon guard added to Guardfile, feel free to edit it
```

This gives you a new file, Guardfile, which contains Guard commands for each of the tools you've added.

Here's what the Guardfile portion for RSpec might look like. This is an edited version of what the Guard plugin provides by default; among other things, I've changed the default command to be Spring-aware:

```
guard :rspec, cmd: "bin/rspec" do
  require "guard/rspec/dsl"
  dsl = Guard::RSpec::Dsl.new(self)

  # Feel free to open issues for suggestions and improvements

  # RSpec files
  rspec = dsl.rspec
  watch(rspec.spec_helper) { rspec.spec_dir }
  watch(rspec.spec_support) { rspec.spec_dir }
  watch(rspec.spec_files)

  # Ruby files
  ruby = dsl.ruby
  dsl.watch_spec_files_for(ruby.lib_files)

  # Rails files
  rails = dsl.rails(view_extensions: %w(erb haml slim))
  dsl.watch_spec_files_for(rails.app_files)
  dsl.watch_spec_files_for(rails.views)
```