3. By default the rails_helper.rb file sets up transactional fixtures. *Fixtures* are a Rails mechanism that defines global ActiveRecord data that is available to all tests. By default fixtures are added once inside a database transaction that wraps all the tests. At the end of the test the transaction is rolled back, allowing the next test to continue with a pristine state. More on fixtures in *Fixtures*, on page 103.

4. Each top-level call to RSpec.describe creates an internal RSpec object called an *example group*. The creation of the example group causes the block argument to describe to be executed. This may include further calls to describe to create nested example groups. The block argument to describe may also contain calls to it. Each call to it results in the creation of an individual test, which is internally called an "example." The block arguments to it are stored for later execution.

5. Each top-level example group runs. By default the order in which the groups run is random. The randomness is to discourage the use of global state that might inadvertently make tests dependent on earlier tests. Before running examples in the example group, run any before(:all) blocks. These blocks allow you to create global setup for all examples in the group. Like anything that contains global setup in tests, they are prone to failure and should be used sparingly.

Running an example group involves running each example that it contains, and that involves a few steps:

1. Run all before(:example) setup blocks. I'll talk about those more in a moment, when they become useful.

2. Run the example, which is the block argument to it. The method execution ends when a runtime error or a failed assertion is encountered. If neither of those happens, the test method passes. Yay!

3. Run all after(:example) teardown blocks. Teardown blocks are declared similarly to setup blocks, but their use is much less common.

4. Roll back or delete the fixtures as described earlier. The result of each example is passed back to the test runner for display in the console or IDE window running the test.

5. After all examples in the file have run, run any after(:all) blocks.

The diagram on page 21 shows the flow.

In your specific case, you have one file, one example group, and one spec, and if you run things, you fail pretty quickly. Here's the slightly edited output.