```
    if credit_card_is_valid? && item.ready_to_ship?
      self.total += item.cost * item.quantity
    end
  end
  self.to_be_paid = self.total - self.amount_paid
  if self.to_be_paid == 0
    self.paid_in_full = true
  end
end
```

This code is a bit of a mess. (It is a special and weird kind of fun to write deliberately awful example code.) It's doing things that should be part of the LineItem class, and it probably could stand to be split. Of course, this example barely scratches the surface of how tangled a poorly written legacy system might be. (You really want to beware the ones with 300-plus-line controller methods.)

This code uses a number of things that are probably attributes that could be set with data, such as amount_paid or item.quantity, but it also calls a few things that could be complex methods in their own rights, such as credit_card_is_valid? or item.ready_to_ship.

A possible test for this code would stub those methods and might look like this (assume we're using factory_bot):

```
Line 1 it "calculates order status" do
  -   order = create(:order, amount_paid: 2.50)
  -   expect(order).to receive(:credit_card_is_valid?).at_least(:once).and_return(true)
  -   item1 = FactoryBot.create(:line_item, quantity: 1, cost: 3.50)
  5   expect(item1).to receive(:ready_to_ship?).and_return(true)
  -   item2 = FactoryBot.create(:line_item, quantity: 2, cost: 5)
  -   expect(item2).to receive(:ready_to_ship?).and_return(false)
  -   order.line_items << [item1, item2]
  -   order.calculate_order_status
 10   assert_equal 3.50, order.total
  -   assert !order.paid_in_full
  - end
```

Lines 2 and 3 set up the order and a mock for the credit_card_is_valid? method. (We're using factory_bot's create method even though it saves to the database, because it's the least likely to disrupt a fragile method.) This can be switched to build_stubbed after the test passes. Lines 4–8 set up individual items, with the action of the test taking place in line 9 and the last lines performing the validation.

In a full test suite you'd test a couple of other combinations of values, so some of the mock setup would probably be extracted to a repeatable method—either an explicit setup block or a method that is called by each test.