client unit tests, 287, 293–295
clients
  creating, 297
  in external service testing, 286, 293–295
code
  for this book, xiv–xv
  mocks as indicator of code quality, 149
  overwriting tests, 81
  separating implementation from test, 37
  tests as, 67
CodeClimate, 284
colon (:)
  data tables, 178
  line numbers in Cucumber, 323
  YAML syntax, 104
comma-delimited lists, fixtures, 106
command line
  Cucumber, 172, 323
  Karma, 193
  returning to in Pry, 314
comments
  breaking up complexity, 82
  pending tests, 80
composing, matchers, 19, 28
compound expressions, 82
compound matchers, 88, 93
constants, verifying doubles, 134
constraints, legacy databases, 354
constructor, 206–207, 211
contain_exactly, 18
container tools, 347
contains, 207
content_tag, 237
continue (Pry), 316
@controller, 228
controller testing, *see also* controllers; system testing
  deprecation in Rails 5, xv, 142, 222, 227
  Gatherer app, 57–59
  as low value, 58
  older controller tests, 227
  redirects, 226
  with request tests, 223–227
  simulating requests in older controller tests, 227
  terms, 152, 223
  views, 233
controllers, *see also* controller testing
  business logic in, 50
  bypassing Rails for speed, 341
  duplication in RESTful, 84
  generating, 46
  integration testing with Minitest, 254–257
  isolating with mocks, 148
  mailer testing, 229–233
  mass assignment testing, 282
  MVC (model-view-controller) diagram, 217
  ordering Gatherer app tasks, 165–171
  preventing form modification, 281
  responsibility, 142
  restricting access, 271–274
  route testing, 219, 259
  separating logic, 240, 342
  simulating database failure with mocks, 138–141
  specifying behavior with mocks, 141–144
  spike for integration testing with Capybara, 164
  system testing, 161
  testing decisions, 50, 57
  testing for failure, 63–66
  user authentication and authorization, 263, 267
  using to limit activities, 279
  view testing and, 233
cookies, 225
costs
  slow tests, 75
  testing, 68–70
:count keyword, 256
count option, 158
create
  controller responsibility, 142
  factories, 116
  Minitest, 248
  model instances, 112
  simulating database failure with mocks, 140
  when to use, 114
create!, 317
created_at, 127
Cucumber
  about, 7
  advanced, 177–179
  explicit step cautions, 179
  features, 173–175
  Guard integration, 330
  installing, 172
  integration testing with, 172–180
  JavaScript drivers, 186
  line numbers, 323
  nondeveloper participation, 180
  Poltergeist with, 186
  running single files, 323
  running smaller groups of tests, 323
  running tests in reverse, 323
  scenario outlines, 178
  Spring integration, 326
  step definitions, 172–179, 292
  tags, 292, 323
  tips, 179
  uses, 172
  VCR and, 292
  version, 172
cucumber command line, 172, 323
cucumber environment, 172
cucumber-rails gem, 172
cucumber.yml file, 172
current_url, 158
current_user, 267
custom assertions, Minitest, 277
custom matchers, 96–99, 277

D

data, *see also* databases
  clarity in tests, 71
  cleanup with let, 26
  creating test data, 101–128
  creating test data with ActiveRecord#create, 101–103
  creating test data with factories, 109–123