```
    it "handles a single string with negative size" do
      creator = CreatesProject.new(
        name: "Project Runway", task_string: "Start Things:-1")
      tasks = creator.convert_string_to_tasks
      expect(tasks.size).to eq(1)
      expect(tasks.first).to have_attributes(title: "Start Things", size: 1)
    end

    it "handles multiple tasks" do
      creator = CreatesProject.new(
        name: "Project Runway", task_string: "Start Things:3\nEnd Things:2")
      tasks = creator.convert_string_to_tasks
      expect(tasks.size).to eq(2)
      expect(tasks).to match(
        [an_object_having_attributes(title: "Start Things", size: 3),
         an_object_having_attributes(title: "End Things", size: 2)])
    end

    it "attaches tasks to the project" do
      creator = CreatesProject.new(
        name: "Project Runway", task_string: "Start Things:3\nEnd Things:2")
      creator.create
      expect(creator.project.tasks.size).to eq(2)
      expect(creator.project).not_to be_a_new_record
    end
  end
end
```

The specs have a progression; each one responds to a limitation of the code at the end of the previous step. In the first spec, an empty string parses to an empty list of tasks. In the next spec, we have a single element with a default size. Next we check for a single element where size is set. Having covered the normal cases, then there are a few specs that test error cases. All those tests call an internal `convert_string_to_tasks` method that allows you to test string parsing separate from any other feature of the class. These tests use the RSpec `has_attributes` matcher to allow you to specify multiple attributes of the same object in one line.

In the error tests, test a series of options for how the size is converted to an integer, such that anything empty or below 1 gets converted to 1. Because the integer conversion has been split out to its own method internally, you could also choose to test that method directly, but right now the internal method is in implementation detail. That might change if the conversion logic got more complex and wound up being a service object of its own.

Then test the case where multiple tasks are separated by a `\n` line separator. This one uses the RSpec `matches` matcher, which takes a data structure and matches the elements one by one. The alternate name `an_object_having_attributes`