- *Type*: Stealth unmanned combat aerial vehicle (UCAV) – Demonstrator
- *Developer*: Northrop Grumman, United States
- *First flight*: February 2011 (Public Unveiling: 2012)
- *Wingspan*: 18.9 m (62 ft)
- *Length*: 11.6 m (38 ft)
- *Maximum speed*: 0.9 Mach (~1100 km/h)
- *Ceiling*: 40,000 ft (12,200 m)
- *Endurance*: 6 hours (extendable with aerial refueling)
- *Propulsion*: Pratt and Whitney F100–220U turbofan
- *Payload capacity*: 2000 lb (900 kg) internal
- *Armament*: GBU-31 JDAM, GBU-12 Paveway II
- *Control system*: Fully autonomous, AI-guided flight management with human oversight
- *Primary roles*: Stealth strike, reconnaissance, autonomous carrier operations

Figure 4.8 shows the Northrop Grumman X-47B, a pioneering stealth UCAV developed under the US Navy's UCAS-D program. The figure highlights the drone's tailless, blended-wing-body design, optimized for stealth and aerodynamic efficiency. The visible foldable wings and retractable landing gear 1enable carrier-based operations, while the internal weapons bay maintains a low radar cross-section. The NAVY insignia and aircraft markings emphasize its naval deployment role. This image captures the X-47B's revolutionary capability for autonomous carrier takeoff, landing, and aerial refueling, showcasing a major milestone in the evolution of autonomous stealth combat aviation.