selects more than one value from the HTML form. Radio box is similar to checkbox but one value can be chosen at a time. File select is the best feature to select one file from the local machine to server machine at a time. Form tag is used to mention a method (POST or GET) and control the entire form controls in the HTML document. Refer Figure 8.1 and 8.2

8.1.1 PHP Basic Form Handling

When the user keys in the input data in HTML controls and clicks the submit button the request will be generated and reaches a PHP file which is mentioned in the FORM tag under the Action attribute. All the input values are synchronized and sent to the server via POST method or GET method. Method is an attribute of form tag in HTML. Once the data reaches the server, two PHP variables such as $_POST and $_GET collects the data and prepares the response accordingly.

Post Method: The input data sent to the server with POST method is stored in the request body of the client's HTTP request.

Get Method: The input data sent to the server with POST method via URL address is known as query string. All input data are visible by user after they click the submit button.

Example:

Test.html:

```
<html>
<body>

<form action=”welcome.php” method=”post”>

Name: <input type=”text” name=”name”><br>
E-mail: <input type=”text” name=”email”><br>
<input type=”submit”>
</form>

</body>
</html>
```

Welcome.php:

```
<html>
<body>
Welcome <?php echo $_POST[“name”]; ?><br>
Your email address is: <?php echo $_POST[“email”]; ?>
</body>
</html>
```


XII CompApp_English version CHAPTER 08.indd 120 23-02-2020 11:49:44