A new user account is added with values to the **user** table using the following INSERT query in MySQL database. The Syntax for inserting record is INSERT INTO table name (Parameter1,Parameter2, Parameter3..) VALUES (Value1, Value2, Value3..); All the query is in SQL will terminate with semicolon(;).

```
mysql> INSERT INTO user (host, name, password, select_priv, insert_priv, update_priv)
VALUES ('localhost', 'guest', PASSWORD('guest123'), 'Y', 'Y', 'Y');
```

Query OK, 1 row affected (0.20 sec) – This statement implies that the query is executed successfully with the time in seconds.

mysql>FLUSH PRIVILEGES;

The above command is executed after every new account creation. This command is similar to rebooting the server so that newly created account and the access privilege are updated in the server. Manual server rebooting is avoided by this command.The inserted record is retrieved using SELECT query and the structure is shown below Table 3.7 & 3.8:

mysql>SELECT * FROM user WHERE name = 'guest';

Table 3.7 Example Table

host	name	password	select_priv	insert_priv	update_priv
localhost	guest	j2gd6vxd1bj3k13g4	Y	Y	Y

Since MySQL is more secured, it provides function to encrypt the password. Thus the password 'guest123' is encrypted and stored as 'j2gd6vxd1bj3k13g4' using PASSWORD() function. The parameters select_priv, insert_priv and update_priv are few privileges set for the new user. If the flag is set as 'Y' then access is granted and if flag set as 'N' then access is denied.

Table 3.8 List of privileges available in MySQL

Privileges	Action Performed (If Granted)
Select_priv	User can select rows from database tables.
Insert_priv	User can insert rows into database tables.
Update_priv	User can update rows of database tables.
Delete_priv	User can delete rows of database tables.
Create_priv	User can create new tables in database.
Alter_priv	User can make changes to the database structure.

3.8.2 Administrative MySQL Command

The Database Administrator (DBA) frequently uses few commands to control the entire database. These commands are known as Administrative MySQL Commands. The following are few such important commands used frequently while working with MySQL.

1. **USE Database** – This command is used to select the database in MySQL for working. If there exists a database named **test**, it is used as working database using the below Syntax.

   Syntax:

```
mysql > use test;
    Database changed
mysql>
```


XII CompApp_English version CHAPTER 03.indd 68 23-02-2020 11:09:47