### Transaction Control Language (TCL)

These SQL commands manage the transactions in SQL databases. It also helps to save the change into database permanently. COMMIT, ROLLBACK, SET TRANSACTION and SAVEPOINT commands belongs to this category. See Table 3.16

**Table: 3.16 SQL TCL COMMANDS List**

| Commands | Description |
|---|---|
| COMMIT | Permanently saves into database. |
| ROLLBACK | Restore database to original form since the last COMMIT. |
| SET TRANSACTION | Sets the transaction properties such as read-write or read only access. |
| SAVE POINT | Used to temporarily save a transaction so that we can rollback to that point whenever required. |

### Data Control Language (DCL)

The SQL commands that implement security on database objects like table, view, stored procedure etc. GRANT and REVOKE commands belongs to this category. See Table 3.17

**Table: 3.17 SQL DCL COMMANDS List**

| Commands | Description |
|---|---|
| **Grant** | used to give permission to specific users on specific database objects like table, view etc. |
| **Revoke** | used to take out permission from specific users on specific database objects like table, view etc. |

## 3.12 Basic SQL Commands

### Create/Drop /Selecting Database

**Create Database** – used to create new SQL Database. The Syntax and example to create studentDB is given below.

**Syntax:** CREATE database databasename;

**Example:** mysql>create database studentDB;

The database created now can be viewed using the following Syntax:

**mysql**>Show databases;

As a result, the newly created studentDB will be listed.

**Drop Database** – used to remove any of the existing SQL Database. The Syntax and example to delete student DB is given below.

**Syntax:** DROP database databasename;

**Example:** mysql>DROP database studentDB;

The deleted database will not be viewed,when we list all databases using the Syntax, Show databases;

**Select Database** – Many databases are available in the repository, from which the suitable database is selected using the below command.

**Syntax:** USE databasename;

**Example: mysql**>USE studentDB;

Once the database is selected, multiple operations are performed as per the needs of the application.



XII CompApp_English version CHAPTER 03.indd 77 23-02-2020 11:09:48