Table:3.20 SQL Delete Record List		
firstname	**lastname**	**age**
Krishna	S	10
Sugal	S	14
Arun	J	15

Syntax2: DELETE from tablename;

Example: mysql>DELETE from Biodata ;

Table:3.21 SQL Delete Record List		
firstname	**lastname**	**age**

Modifying Record

SQL provides us with modifying and updating the existing records in a table using UPDATE command. The age of Krishna in Biodata table is changed using the below Syntax.

Syntax1: UPDATE tablename

SET column1="new value"

Where column2="value2";

Example: mysql>UPDATE Biodata SET age=13 WHERE firstname="Krishna";

WHERE Clause

In SQL command WHERE clause is used to specify the selection criteria Based on that data's are retrieved or modified as per the query. In the WHERE conditions, operations like =, !=, >, >=, < , <= are used to frame the query statement. WHERE clause is used in SELECT and UPDATE query statement for the condition. The number of records updated in a table depends on the WHERE condition.

Using Operators

While forming the SQL query we use major operators like Arithmetic, Comparison and Logical in the WHERE clause. The purpose of each operator is listed below in Table 3.22.

Table:3.22 MySQL Operators	
Operator Type	**Operator**
Arithmetic Operator	+, -, *, /, %
Comparison Operator	=, !=, <, >, <>, >=, <=,
Logical Operator	AND, ANY, BETWEEN, EXISTS, IN, LIKE, NOT, OR, UNIQUE

Sorting Records

The Query results are listed in Ascending or Descending order using the command ORDER BY clause. In some databases the results are sorted by default in Ascending order and is given in Syntax1. The results are displayed in descending order as per Syntax2. See Table 3.23 and 3.24

Syntax1: select * from tablename ORDER BY columnname;

Example: select * from Biodata ORDER BY firstname;

Table:3.23 Select Record List		
firstname	**lastname**	**age**
Arun	J	15
Krishna	S	13
Sugal	S	14

XII CompApp_English version CHAPTER 03.indd 79 23-02-2020 11:09:48