எடுத்தக்காட்டு 15.3.2 -1

```
import sqlite3
connection = sqlite3.connect ("Academy.db")
cursor = connection.cursor()
# delete
cursor.execute ("""DROP TABLE Student;""")
sql_command = """
CREATE TABLE Student (
Rollno INTEGER PRIMARY KEY , Sname VARCHAR(20), Grade CHAR(1),
gender CHAR(1), Average DECIMAL (5, 2), birth_date DATE);"""
cursor.execute(sql_command)
    sql_command = """INSERT INTO Student (Rollno, Sname, Grade, gender, Average, birth_
    date) VALUES (NULL, "Akshay", "B", "M","87.8", "2001-12-12");""" cursor.execute(sql_
    command)
    sql_command = """INSERT INTO Student (Rollno, Sname, Grade, gender, Average,
    birth_date) VALUES (NULL, "Aravind", "A", "M","92.50","2000-08-17");""" cursor.
    execute(sql_command)
# never forget this, if you want the changes to be saved:
connection.commit()
connection.close()
print("STUDENT TABLE CREATED")
```

வெளியீடு

```
STUDENT TABLE CREATED
```

பின்வரும் எடுத்துக்காட்டு 15.3.2 ஒரு முழுமையான உதாரணமாகும். இந்த நிரலை இயக்க "Academy.db" கோப்பை வேண்டும் அல்லது SQL கட்டளையில் உள்ள DROP TABLE என்ற வரியின் குறிப்புரையாக்குக.

பெரும்பாலான நிகழ்வுகளில் கருத்தியலாக ஒரு SQL அட்டவணையில் தரவுகளை இடையில் செருக முடியாது. Insert கூற்றைப்பயன்படுத்தி, சில பைத்தான் தரவு இனங்களில் உள்ள பலத்தரவுகளை உள்ளிடலாம்.

பின்வரும் எடுத்துக்காட்டில், Academy.db என்ற தரவுத்தளம் மற்றும் Student அட்டவணை ஏற்கனவே உள்ளது எனக்கொள்க. நபர்களின் தரவுகளைக்கொண்ட List-யைINSERT கூற்றைப் பயன்படுத்தி உள்ளிடப்பட்டுள்ளது.

Chapter 15.indd 298 30-01-2020 20:58:05