phone_app directory that you created earlier in this chapter. Add the following content to it (the field comments are for your reference and don't need to be typed out in your file):

phone_app/lib/phone_app/conversations/schema/sms_message.ex

```
Line 1  defmodule PhoneApp.Conversations.Schema.SmsMessage do
        use Ecto.Schema

        @timestamps_opts [type: :utc_datetime_usec]
  5     schema "sms_messages" do
          # 1-to-many relationship with the other person in the conversation
          belongs_to :contact, PhoneApp.Conversations.Schema.Contact

          # Holds the message identifier for Twilio's message objects.
 10       field :message_sid, :string
          # Holds the account identifier that interacted with Twilio.
          field :account_sid, :string

          # Holds the full text contents of the SMS message.
 15       field :body, :string
          # The phone number that sent the SMS message.
          field :from, :string
          # The phone number that received the SMS message.
          field :to, :string
 20
          # Holds the current state of the SMS message from Twilio.
          field :status, :string
          # Whether this message was received inbound or sent outbound.
          field :direction, Ecto.Enum, values: [:incoming, :outgoing]
 25
          timestamps()
        end
      end
```

Our module starts with a use statement on line 2 that brings the Ecto schema macros into our module. Without this line, the schema/2 function would be undefined and our code wouldn't compile. The schema/2 function on line 5 says that our database table is called sms_messages and its data definition is defined inside of the do block.

Inside of the do block, we use the field macro function to define the individual fields of our data structure. A comment describing each field is included, so you can see how the field fits into our data structure. We'll come back to the belongs_to function later in this section.

We use timestamps/0 to define inserted_at and updated_at fields that Ecto manages for us. When you add a record to the database, Ecto will automatically set inserted_at for you. And when you update the record, the updated_at column will be set.