Execute the following commands to copy important files over. The prefix code refers to the folder you just downloaded. Run this in the phone_app project folder that you started in the previous chapter.

```
$ cp code/phone_app/priv/repo/seeds.exs priv/repo/seeds.exs
$ cp code/phone_app/priv/repo/delete_seeds.exs priv/repo/delete_seeds.exs
$ cp code/phone_app/lib/phone_app_web/components/layouts/app.html.heex
     lib/phone_app_web/components/layouts/app.html.heex
$ cp -R code/phone_app/lib/phone_app_web/controllers/message_html
        lib/phone_app_web/controllers
$ cp code/phone_app/lib/phone_app/conversations/schema/new_message.ex
     lib/phone_app/conversations/schema/new_message.ex
```

Add the following dependencies to mix.exs at the end of the deps/0 function and then run mix deps.get:

phone_app/mix.exs

```
{:ex_phone_number, "~> 0.3"},
{:faker, "~> 0.17", only: [:dev, :test]},
```

Run the seeds.exs script that you just grabbed from the code listing. A "seed script" is a script that sets up test data for local use. Our script creates records for 500 different SMS messages between 20 different phone numbers.

At this point, you should be able to start the app with minimum warnings:

```
$ mix run priv/repo/delete_seeds.exs
$ mix run priv/repo/seeds.exs
```

You'll see warnings about missing routes at this point. We'll fix those up throughout the chapter.

Port 4004 Instead of 4000

Update your config/dev.exs file to point to port 4004 instead of 4000:

phone_app/config/dev.exs

```
config :phone_app, PhoneAppWeb.Endpoint,
  http: [ip: {127, 0, 0, 1}, port: 4004],
```

This change will remove potential headaches where your application is running on the default port that may already be in use. The rest of this book will assume port 4004 for all requests.

Let's finally get started with Phoenix. We'll start by looking at the request lifecycle, and then we'll write our controller.