In addition, add the following line to the Conversations module:

phone_app/lib/phone_app/conversations/conversations.ex
```
defdelegate new_message_changeset(params),
  to: Schema.NewMessage,
  as: :changeset
```

The show function is fairly straightforward. We use the context functions to query for our data and to set up a changeset. (You copied the NewMessage module into the app earlier in this chapter.)

We won't cover the entire NewMessage changeset, but it follows a powerful pattern for forms:

phone_app/lib/phone_app/conversations/schema/new_message.ex
```
defmodule PhoneApp.Conversations.Schema.NewMessage do
  use Ecto.Schema
  import Ecto.Changeset

  embedded_schema do
    field :to, :string
    field :body, :string
  end

  def changeset(attrs) do
    fields = [:to, :body]
    attrs = force_country_code(attrs)

    %__MODULE__{}
    |> cast(attrs, fields)
    |> validate_required(fields)
    |> validate_change(:to, &validate_phone_number/2)
  end

  # ...data functions below
end
```

This schema and changeset don't write data to the database. They only validate data and turn it into a predictable format. The Phoenix form helpers know how to work with this data to create a form. It all fits together pretty seamlessly!

If you load the app at this point, you'll see an error that "no show html template defined for PhoneAppWeb.MessageHTML." We need to create a view that Phoenix can use to render HTML.

Create a file at phone_app_web/controllers/message_html.ex with the following contents:

phone_app/lib/phone_app_web/controllers/message_html.ex
```
defmodule PhoneAppWeb.MessageHTML do
  use PhoneAppWeb, :html

  embed_templates "message_html/*"
end
```