You could change this line to change the port that Phoenix dev environment runs on.

This configuration alone doesn't actually start a server. The `mix phx.server` command that we run has special instructions[19] that tell Phoenix to start a server. It looks something like this:

```
def run(args) do
  Application.put_env(:phoenix, :serve_endpoints, true, persistent: true)
  Mix.Tasks.Run.run(open_args(args) ++ run_args())
end
```

Because you have to explicitly tell Phoenix to start a server, one of the big mistakes that people make when deploying a Phoenix app isn't starting the server. This has largely been fixed by clearer documentation in the Phoenix deployment guides and generated code that configures it correctly. But keep an eye on this if you notice that your application is starting without a web server.

Let's briefly talk about bundling and serving static assets in Phoenix.

Manage Static Assets

Phoenix takes a hands-off approach to your asset pipeline. This lets you build and bundle your JavaScript, CSS, images, fonts, and other assets the way that you want to. It would be a bit cumbersome if there wasn't some way to manage assets out of the box, so the `phx.new` generator sets up a basic asset pipeline for you.

Phoenix 1.7 installs an esbuild-powered[20] asset pipeline. Esbuild is an asset bundler that's extremely fast and doesn't rely on external languages to be installed. It dramatically simplifies the development and deployment of assets when compared to Webpack-based pipelines.

The Phoenix generator also sets up Tailwind CSS[21] for you. Tailwind is a class-based CSS library that has become very popular. Tailwind lets you apply styles directly in your HTML instead of writing custom CSS. (I personally love Tailwind.)

The asset pipeline is configured inside of the `config.exs` file. You can see the relevant lines here—these are already in your project so you don't need to type anything out:

19. https://github.com/phoenixframework/phoenix/blob/v1.7.6/lib/mix/tasks/phx.server.ex
20. https://esbuild.github.io/
21. https://tailwindcss.com/