phone_app/config/config.exs

```
# Configure esbuild (the version is required)
config :esbuild,
  version: "0.17.11",
  default: [
    args:
      ~w(
        js/app.js
        --bundle
        --target=es2017
        --outdir=../priv/static/assets
        --external:/fonts/*
        --external:/images/*
      ),
    cd: Path.expand("../assets", __DIR__),
    env: %{"NODE_PATH" => Path.expand("../deps", __DIR__)}
  ]

# Configure tailwind (the version is required)
config :tailwind,
  version: "3.2.7",
  default: [
    args: ~w(
      --config=tailwind.config.js
      --input=css/app.css
      --output=../priv/static/assets/app.css
    ),
    cd: Path.expand("../assets", __DIR__)
  ]
```

Plus, the dev environment will automatically reload assets using watcher scripts:

phone_app/config/dev.exs

```
watchers: [
  esbuild:
    {Esbuild, :install_and_run, [:default, ~w(--sourcemap=inline --watch)]},

  tailwind:
    {Tailwind, :install_and_run, [:default, ~w(--watch)]}
]
```

You don't need to worry about changing these options until you have specific asset needs—they work great out of the box.

The most important part of the asset pipeline is the output directory. Phoenix expects to find assets in the priv/static/assets folder. The generator sets this up properly, but keep this in mind if you choose to use another asset pipeline tool like Webpack.