Component Attributes

Here's the MessageHTML module that we defined earlier in this chapter:

phone_app/lib/phone_app_web/controllers/message_html.ex
```
defmodule PhoneAppWeb.MessageHTML do
  use PhoneAppWeb, :html

  embed_templates "message_html/*"
end
```

The use of embed_templates automatically turns any templates in the folder into a component. We have an HTML file located at lib/phone_app_web/controllers/message_html/message_form.html.heex, so this makes a message_form component available for us to use.

We use this component like so:

phone_app/lib/phone_app_web/controllers/message_html/show.html.heex
```
<li class="w-full">
  <.message_form changeset={@changeset} contact={@conversation.contact} />
</li>
```

We also use it like so:

phone_app/lib/phone_app_web/controllers/message_html/new.html.heex
```
<div class="mt-4">
  <.message_form changeset={@changeset} contact={nil} />
</div>
```

These files were included with the files you copied in, so you have them in your project, but you may not have looked through them yet.

This component is pretty simple to use, but it would benefit from defining the attributes that can go into it. Let's do so by modifying the MessageHTML module:

phone_app/lib/phone_app_web/controllers/message_html.ex
```
# Define the attributes that go into the message_form component, located
# inside of the templates directory.
alias PhoneApp.Conversations

attr :changeset, Ecto.Changeset, required: true
attr :contact, Conversations.Schema.Contact, required: false, default: nil

def message_form(assigns)
```

Yes, this function head without a body is intentional! The Phoenix.Component code picks this up and associates the attributes to the correct component. This means that you can define multiple components inside of the same file.