The function Application.fetch_env!/2 on line 3 returns the values that you configured in the dev.secret.exs config file. Everything inside of your config files is available to your application, so it's straightforward to use for application configuration.

Our config is defined as a keyword list, so we use the Keyword module to access individual values. You'll see on line 9 that the base_url value can be overridden via a function parameter. This pattern is extremely useful for testing, as you can swap out the URL for a library like Bypass.[9]

Finally, we use Req.new/1 on line 14 to configure a base set of options for our HTTP client. This lets us make API calls without having to set the options on each individual request. You'll see how clean this makes our API functions.

Add the following functions to the top of the file:

phone_app/lib/phone_app/twilio/api.ex

```
Line 1  def get_sms_message!(params, client \\ req_client()) do
        %{account_sid: account, message_sid: id} = params

        Req.get!(client, url: "/Accounts/#{account}/Messages/#{id}.json")
    5 end

      def send_sms_message!(params, client \\ req_client()) do
        account_sid = Keyword.fetch!(twilio_config(), :account_sid)
        %{from: from, to: to, body: body} = params
   10   body = %{From: from, To: to, Body: body}

        url = "/Accounts/#{account_sid}/Messages.json"
        Req.post!(client, url: url, form: body)
      end
```

These functions make HTTP calls to our API. Req provides a set of common HTTP functions such as Req.get!/2, Req.post!/2, Req.put!/2, and so on. These functions are quite easy to use!

We pass the form option to Req.post! on line 13. This encodes the body as a URL-encoded form. We could use the json option instead, but the Twilio API requires the form encoding to be used.

There is one unusual bit of syntax that you haven't seen before. In both of our function heads, we define client \\ req_client(). This isn't a typo—Elixir's default function arguments can invoke other functions! Each time that the function is invoked without a client argument provided, the req_client/0 function is called and passed into the function.

We won't cover it in this book, but you can completely customize any step of the Req request lifecycle. You could swap out the HTTP library that it

9. https://hexdocs.pm/bypass/Bypass.html