We first have to update our Gemfile to include the Webpacker gem:

```
gem 'webpacker', '~> 3.5'
```

Then we run bundle install via rebuilding our image:

```
$ docker-compose build web
```

Let's stop the web service because it's currently running our old version without the Webpacker gem installed:

```
$ docker-compose stop web
```

Now we can install Webpacker in our app:

```
$ docker-compose run web bin/rails webpacker:install
```

inotify Overflow Error



Unfortunately, when running the previous command, you may encounter the following error message, which appears to be caused by a bug in the rb-inotify gem:[2]

```
run() in thread failed: inotify event queue has overflowed.
```

Although unsightly, it doesn't seem to have any material impact, and you can safely ignore it.

followed by the Webpacker React integration:

```
$ docker-compose run web bin/rails webpacker:install:react
```

OK, our app is configured for Webpacker and React. However, before we can truly say we're done, we need a way to compile our React assets automatically.

Compiling Assets with Webpacker

As part of Webpacker, Rails provides the webpack-dev-server binary. This is a small server that runs in the background, automatically compiling our webpack-managed files.

If you were developing locally, this would just be another command you'd issue from your terminal. However, the Docker way is to run this as a separate service in its own container.

Let's add a new service for it to our docker-compose.yml file:

2. https://github.com/guard/rb-inotify/issues/61