Let's add it to our Gemfile now:

```
group :development, :test do
  # Call 'byebug' anywhere in the code to stop execution and get a debugger…
  gem 'byebug', platforms: [:mri, :mingw, :x64_mingw]
  gem 'rspec-rails', '~> 3.8'
➤ gem 'capybara', '~> 3.7'
end
```

Next we need to install this new gem by rebuilding the image. We'll recreate the web container at the same time:

```
$ docker-compose build web
$ docker-compose stop web
$ docker-compose up -d --force-recreate web
```

We're now ready to create our first system spec. By default, RSpec expects to find these in the spec/system directory, so let's create this now:

```
$ mkdir spec/system
```

Let's start by creating the file spec/system/page_views_spec.rb and edit it as follows:

```
require 'rails_helper'

RSpec.describe "PageViews" do
  it "shows the number of page views" do
    visit '/welcome'
    expect(page.text).to match(/This page has been viewed [0-9]+ times?!/)
  end
end
```

Linux Users: File Ownership



Again, you will have to chown the files (see File Ownership and Permissions, on page 199):

```
$ sudo chown <your_user>:<your_group> -R .
```

Before we run this test, let's switch to using the RackTest driver for standard system tests. Not only is this faster, but it saves us having to install a full browser driver with JavaScript support (Selenium is the default) until we actually need it.

Edit spec/rails_helper.rb, adding the following lines just before the final end:

```
config.before(:each, type: :system) do
  driven_by :rack_test
end
```

This uses RSpec's before configuration hook to perform some of the setup before every system spec is run; specifically, we use the driven_by method—a