a port mapping so that the VNC server running inside the container on port 5900 is reachable from outside the container on that same port. You can check out Docker's docs for more details on the logging options available.[18]

Let's start our new service so Selenium Chrome is available for our system tests:

```
$ docker-compose up -d selenium_chrome
```

Problems Starting Chrome?



If you get an error when starting the selenium_chrome service, it's likely because you have another VNC client running on port 5900. For example, on macOS, make sure you have Screen Sharing turned off in your System Preferences.

Next, we have to configure Capybara to use Chrome running in a container. Let's create the file spec/support/capybara.rb and add the following config:

```
Line 1 Capybara.register_driver :selenium_chrome_in_container do |app|
  2   Capybara::Selenium::Driver.new app,
  3     browser: :remote,
  4     url: "http://selenium_chrome:4444/wd/hub",
  5     desired_capabilities: :chrome
  6 end
```

This registers a new driver with Capybara—called :selenium_chrome_in_container—configured to use the Selenium driver to control a remote Selenium instance of Chrome running at http://selenium_chrome:4444/wd/hub (line 5.) Why this specific URL? Selenium listens for incoming client requests at http://<host>:<port>/wd/hub. Port 4444 is the default port that Selenium listens on, and the hostname selenium_chrome, which matches our new service in docker-compose.yml, will reach our container running Chrome. You may recall from Chapter 5, Beyond the App: Adding Redis, on page 59, that Compose sets up hostnames to reach other Compose services.

Linux Users: File Ownership



As always, remember to chown the new file (see File Ownership and Permissions, on page 199):

```
$ sudo chown <your_user>:<your_group> -R .
```

Configuring RSpec System Tests

We've created a new Capybara driver, but how do we configure RSpec to use it?

18. https://docs.docker.com/compose/compose-file/#logging