where <IP address of instance>, in our case, is local-vm-1's public IP address. We can easily find that out by rerunning:

```
$ docker-machine ls
NAME         …   …   …   URL                         …   …   …
local-vm-1   *   …   …   tcp://192.168.99.100:2376       …
```

The IP address of the instance is listed in the "URL" column. For me, the IP address is 192.168.99.100, but yours will differ.

Let's go ahead and run this now (substituting the correct IP):

```
$ docker swarm init --advertise-addr 192.168.99.100
Swarm initialized: current node (kun8mrdiuhewsydse3exvdq4a) is now a manager

To add a worker to this swarm, run the following command:

    docker swarm join --token SWMTKN-1-64vcnpwr3sv6pco6ha8fyzm3pbi71h72cqq89
owty12uvlrd80-a0g240eqg899rbidxnw7q3fa4 192.168.99.100:2377

To add a manager to this swarm, run 'docker swarm join-token manager' and
follow the instructions.
```

For now, we're going to stick with a single-node Swarm cluster. However, you'll notice in the output instructions for connecting more instances to the swarm—we'll come back to this later.

OK, single-node swarm at the ready. How do we deploy our application to it?

Describing Our App to Swarm

You're probably becoming pretty comfortable describing our app as a set of services defined in a Compose file. However, a docker-compose.yml file is *development-focused*; it lets us rebuild images easily and not get bogged down in unnecessary details such as deployment configuration. However, now when we come to deployment, we need something that is *deployment-focused*.

Swarm introduces the concept of a *stack* to mean an application made up of a group of services that are *capable of being deployed*. We describe our stack to Swarm with a deployment-focused variant of a Compose file known as a *stack* file. Although you'll sometimes still hear this referred to as a Compose file, we'll stick with the latter since it clearly distinguishes it from a normal Compose file.

Ready to create your first stack file? Copy our docker-compose.yml file to one called docker-stack.yml, then modify it so it looks as follows: