```
$ docker-machine ssh local-vm-1
```

and issued commands against it from our local shell session:

```
$ docker-machine ssh <instance name> "<command>"
```

3. We saw how to configure our Docker Client to target the Docker Engine on our virtual instance:

```
$ eval $(docker-machine env local-vm-1)
```

and to reset it again with:

```
$ eval $(docker-machine env -u)
```

4. We turned our vanilla Docker instance into a single-node swarm cluster:

```
$ docker swarm init --advertise-addr <IP address of instance>
```

5. Having created a production version of our docker-compose.yml called docker-stack.yml, we deployed our application on the swarm as a stack using:

```
$ docker stack deploy -c docker-stack.yml myapp
```

6. We saw how to list the services in our stack with:

```
$ docker stack services myapp
```

or list all services on the swarm with:

```
$ docker service ls
```

7. We saw how to deploy an updated version of the app:

```
$ docker stack deploy -c docker-stack.yml myapp
```

8. We scaled up our web service by running multiple containers, utilizing Swarm's built-in load balancing:

```
$ docker service scale myapp_web=<n>
```

Not too shabby.

Now that we've started to get a feel for Docker Machine and Swarm, and have seen how to deploy and scale our application, it's time to move into the big leagues. In the next chapter, we'll finally move off our local machine and into the big, wide world that is the cloud.