Capture the swarm token that will be given in the output.

6. Create two instances and connect them to the swarm:

```
SWARM_TOKEN=SWMTKN-1-3nzypy20thm9zd1whfsyu4kcmhxfnyo6hbivrgbec5yyz2o9yq-2
zvdcauxzl1ncs75oe8775qdg
for i in 1 2
do
  # create the node
  docker-machine create \
    --driver amazonec2 \
    --amazonec2-open-port 80 \
    --amazonec2-region eu-west-2 \
    aws-worker-$i

  # add ubuntu user to `docker` group
  docker-machine ssh aws-worker-$i \
    'sudo usermod -a -G docker $USER'

  # join the swarm
  docker-machine ssh aws-worker-$i \
    "docker swarm join --token $SWARM_TOKEN 172.31.29.132:2377"
done
```

7. Point our CLI to the manager:

```
eval $(docker-machine env aws-manager-1)
```

8. Update security group to allow swarm ports.

   Docker's docs say that Swarm needs the following ports to be open:[14]

   - TCP port 2377 for cluster management communications
   - TCP and UDP port 7946 for communication among nodes
   - UDP port 4789 for overlay network traffic

   With DigitalOcean, these ports were open by default. However, with AWS, it's a little more complicated. Docker Machine instances are added to a security group called docker-machine, which restricts incoming connections (ingress) to a small number of ports that don't include those listed above. For Swarm to work correctly, we must add them.

   Log in to the AWS Console, and go to EC2 > security groups. Click on the docker-machine security group, then on its Inbound Rules tab. Here, click to edit the rules and add the missing rules. It's possible to automate this process using the AWS CLI.[15]

14. https://docs.docker.com/engine/swarm/swarm-tutorial/#open-protocols-and-ports-between-the-hosts
15. https://semaphoreci.com/community/tutorials/bootstrapping-a-docker-swarm-mode-cluster