9. Deploy the app:

```
$ docker stack deploy -c docker-stack.yml myapp
```

10. You should now be able to reach the app by visiting http://ip address of a node/welcome. You can list the node IPs by doing:

```
$ docker-machine ls
```

Remember to Turn Out the Lights



When you're done trying things out in this chapter, remember to stop or delete your cloud instances to avoid continued charges.

To stop your instances, you can run:

```
$ docker-machine stop <instance 1> <instance 2> ...
```

or to completely remove them, run:

```
$ docker-machine rm <instance 1> <instance 2> ...
```

Quick Recap

Excellent! We've been Docker Machining and Swarming like a boss. We've deployed our application to not one, but two cloud providers, creating the infrastructure we needed as we went.

To recap:

1. We covered the steps necessary to create a multinode Swarm cluster on DigitalOcean or AWS.
2. We deployed our application to the Swarm cluster by making our Docker CLI target the manager node:

   ```
   $ eval $(docker-machine env do-manager-1)
   ```

   and then deploying the application:

   ```
   $ docker stack deploy -c docker-stack.yml myapp
   ```

3. We used the visualizer to see the placement of containers on our nodes.
4. We learned about deploy: options that can be specified in our docker-stack.yml file, including placement constraints.[16]
5. We scaled up the service using both the command:

   ```
   $ docker service scale myapp_web=3
   ```

16. https://docs.docker.com/engine/reference/commandline/service_create/#specify-service-constraints---constraint