Index

SYMBOLS

"$@" syntax, 123
* (asterisk) for active instance, 159
- (dash) for active instance, 159
. (period)
  indicating current directory, 23
  mounting a local volume, 50

A

-a option, 10
abort error, 124
ACI (Azure Container Instances), 141
adapter pattern, 136
(AKS) (Azure Kubernetes Service), 139
alerts, operations role, 130
Amazon AWS
  account, 184
  deploying to, 173, 184–186
  Elastic Container Registry, 153
  Elastic Container Service, 134, 137, 139, 196
  Elastic Container Service for Kubernetes (EKS), 138–139
  Fargate, 141
  Lambda, 140
  Management Console, 137
  provisioning IaaS, 135
  snapshotting, 196
Ansible, 136
API endpoints, 88
API token for DigitalOcean, 174
apps
  connecting to Redis, 64–67
  connecting to database, 75–79
  describing to Swarm with stack file, 161–165
  directories for, 11
  generating without Ruby installed, 10–15
  holistic view, xiii–xiv
  launching in background with detached mode, 49
  launching with Compose, 47–50
  restarting on failure, 194
  running in containers, 17–29
  version numbers in Compose file, 46
apt-get, 20, 37
apt-transport-https, 89
asset pipeline, 22, 88
assets
  compiling with webpacker, 90–92
  precompiling in image, 147
  static assets, 146
asterisk (*) for active instance, 159
attached mode, 124
attaching, 49
autopilot pattern, 196
autoscaling, 133, 191
AWS, *see* Amazon AWS
AWS_ACCESS_KEY_ID, 184
AWS_DEFAULT_REGION, 184
AWS_SECRET_ACCESS_KEY, 184
Azure
  Container Instances (ACI), 141
  Container Registry, 153
  Kubernetes Service (AKS), 139
  provisioning IaaS, 135

B

-b option, 25, 28
backups, 196
Barman, 196–197
base images, 20
Bash
  compound run, 18
  entrypoints workaround, 123
  input options, 15
  running in containers, 10–12
  stopping, 12
  terminal emulator option, 15
blue-green deployment, 130, 191
boot2docker, 157
breakpoints, 109
bridge network, 63