sharing images, 148–154
Swarm, 160–171
Prometheus, 191
prompt option, 20
provisioning
with CloudFormation, 137
with Docker Machine, 135
IaaS, 135–136
operations role, 130
proxying, 192
prune, 56
pruning, 56
ps, 9, 29, 52, 168
psql, 74
publishing, ports, 26, 61
Puppet, 136
push, 152
pushing images, 151–154
PyInstaller, 124

Q

\q <Enter>, stopping Postgres client, 74
-qq option, 20
Quay, 153
quiet option, printing, 20
quit, 62

R

RackTest driver, 100, 102
Rails, *see also* Rails server
advantages, xiii
asset pipeline, 22, 88
installing Rails gem, 11
system tests, 99–101, 104–109
version, 11
Rails apps, *see* apps
rails new, 12
Rails server
binding to IP addresses, 28
errors, 110, 121–123
logs, 54
restarting for Postgres, 79
running, 25
starting with Compose, 49
startup error, 50–51
stopping, 26, 67
RAILS_ENV, 146
RAILS_LOG_TO_STDOUT, 146
RAILS_SERVE_STATIC_FILES, 146
React, 87–93
README file caching example, 38–41
recreation, forcing, 79
Redis, 59–69
about, 59
command-line interface, 62
connecting to apps, 64–67
installing gem, 64
page hits example, 65–68
server, manually connecting, 62
server, starting, 60–62
server, stopping, 60, 67
starting connected app with Compose, 67
redis gem, 64
redis-cli, 62
registries, 149–154
release management
operations' role, 130
orchestrators' role, 132
removing, *see* deleting
replica containers, 166
ReplicaSets, 133
repositories
images, 149–154
names, 150
private, 149, 152
tagging images, 151
repository name tag, 150
require, 105
resources
limiting, 190
pruning unused, 56
resources for this book
Compose, 4
Docker, xv, xvii
installation, 4
logs, 54
security, 192
sources of images, 201–203
VirtualBox, 156
restart, 53
restart policy, 194
restarting, containers, 52–53, 193
rm (Compose), 56, 83
rm command, 10
--rm option, 10, 34, 78
root user as default, 11
rotating secrets, 193
RSpec
about, 95
debugging, 109
first test, 97–99
headless testing, 108
installing, 97
JavaScript tests, 101–109
setup, 96
system tests, 99–101, 104–109
viewing tests, 103, 106
Ruby
generating apps without Ruby installed, 10–15
running scripts without Ruby installed, 7–10
RubyMine, 110
run, *see also* docker-compose run
compound, 18
generating apps without Ruby installed, 10–15
running Ruby scripts, 7–10
running a Rails server with images, 25
starting a Redis server with, 60
using, 7–10
RUN instruction, 20
run() in thread failed error, 90
runtime
Docker advantages, xiv
mounted volumes, 21

S

scaling
autoscaling, 133, 191
costs, xv
Docker advantages, xiv–xv
down, 183
horizontal, 181
with Swarm, 167–171, 181–183
scenario, 102
schedulers, 196
scratch, 20
Screen Sharing, 104, 106
secret command, 193
secret management, 132, 193
SECRET_KEY_BASE, 146
security
containers, 192