cookies, 146
deploying to AWS, 185
extracting environment variables into separate files, 77
Fargate, 141
hosting internal repositories, 153
images, 192, 202
not publishing ports, 61
orchestrators, 132
ports, 192
Postgres environment variables, 77
Postgres password, 73
resources on, 192
secret management, 193
Selenium
headless testing, 108
installing, 103
JavaScript tests, 102–109
selenium-webdriver gem, 103
selenium/standalone-chrome-debug image, 103
server is already running error, 121
server.pid errors, 121–123
serverless computing, 140–141
servers, *see also* Rails server
compiling assets with webpacker, 90–92
Postgres, starting, 71–73
publishing ports, 27
Redis, manually connecting, 62
Redis, starting, 60–62
Redis, stopping, 60, 67
VNC, 103, 106
--service-ports option, 109
services
adding example of Postgres, 71–85
adding example of Redis, 60–62
deploying with swarms, 165–167
describing with Compose, 45
detached mode, 73
DNS resolution, 64
forcing recreation, 79
hostnames, 64
launching apps with Compose, 47–50
listing services deployed to a swarm, 166
listing tasks for specific services, 168
names, 64, 88
placement constraints, 180
replica containers, 166
scaling, 168–171, 181–183
separating database services, 163
specifying image to be used, 61
starting and stopping with Compose, 51–53
updating image, 170
services collection, 46
session affinity, 191
set, 123
setup, *see also* installation
Docker advantages, xiv
RSpec, 96
testing, 96
shell
compound run, 18
entrypoints workaround, 123
input options, 15
running in containers, 10–12
Shell form of CMD, 34
stopping, 12
terminal emulator option, 15
SIGKILL, 52
SIGTERM, 52
--skip-bundle option, 12
--skip-test option, 12
sleep, 107
snapshotting, 196
specs, *see* RSpec
SSH, 157, 175, 184
Stable form of Community Edition, 3
stack command, 166
stack file
about, 161
using, 161–165
stacks
about, 133, 161
defined, 161
deploying, 170
using, 161–165
start, 53
starting image, 19
static assets, 146
statistics, 194
stats, 194
stderr, attaching, 49
stdin, attaching, 49
stdout, attaching, 49
sticky sessions, 191
stop, 49, 52, 67, 124
stopping
Compose, 49
container log stream, 54
containers, 12, 49, 52, 56, 124
instances when deploying to cloud, 186
Postgres client, 74
Rails server, 26, 67
Redis client, 62
Redis server, 60, 67
services with Compose, 51–53
shell, 12
sudo, 21
Swarm, 160–171
about, 160
continuous deployment, 191
deploying with, 165–167, 173–178, 191
deploying with DigitalOcean, 173–178
vs. Kubernetes, 132
limiting resources, 190
restarting on failure, 194
scaling, 167–171, 181–183
secrets, 193
single-node, 160–167
stack file, 161–165
tasks, 167–171
visualizing containers, 179–183
swarm command, 160
swarms
creating on DigitalOcean, 173–178
defined, 160
deploying to DigitalOcean, 178–183
deploying with, 165–167
initializing when deploying to AWS, 184
joining workers to, 177
scaling, 167–171
secrets, 193
single-node example, 160–167