Finding the IP Address of a Running Container



If you're curious how you'd find out the actual IP address of a running container, you can do it as follows:

1. Get the container ID:

```
$ docker ps
CONTAINER ID        IMAGE               «more info»
d7230c4b0595        e28cf982ae39        «.........»
```

2. Use this docker inspect command specifying the container ID:

```
$ docker inspect --format \
    '{{ .NetworkSettings.IPAddress }}' d7230c4b0595
172.17.0.2
```

Quick Recap

Wow, what an action-packed chapter! Let's review the highlights:

1. We saw our first, rough-and-ready Dockerfile designed to allow us to run our app with a Rails server:

```
FROM ruby:2.6

RUN apt-get update -yqq
RUN apt-get install -yqq --no-install-recommends nodejs

COPY . /usr/src/app/

WORKDIR /usr/src/app
RUN bundle install
```

2. We built our custom image from this Dockerfile with:

```
$ docker build .
```

3. We listed the images on our system by issuing:

```
$ docker images
```

4. We started up a Rails server to run our app with:

```
$ docker run -p 3000:3000 a1df0eddba18 \
 bin/rails s -b 0.0.0.0
```

And we saw it running in a browser on http://localhost:3000.

In the next chapter, we'll start to make some further refinements to our Dockerfile. In the process, we'll learn how to give our images friendly names, and speed up image builds by taking advantage of the built-in caching mechanism.