Next, Compose creates and starts a single container for our web service based on the image it has just created. It will name containers using the format <appname>_<service name>_<n>:

```
Creating myapp_web_1 ... done
```

In a process known as *attaching*, Compose then connects our local IO streams (stdin, stdout, and stderr) to the running container, so we can see its output:

```
Attaching to myapp_web_1
```

As a result, we're able to see our Rails server starting inside the container:

```
web_1  | => Booting Puma
web_1  | => Rails 5.2.2 application starting in development
web_1  | => Run `rails server -h` for more startup options
web_1  | Puma starting in single mode...
web_1  | * Version 3.12.0 (ruby 2.6.0-p0), codename: Llamas in Pajamas
web_1  | * Min threads: 5, max threads: 5
web_1  | * Environment: development
web_1  | * Listening on tcp://0.0.0.0:3000
web_1  | Use Ctrl-C to stop
```

The Rails server launched thanks to the default CMD instruction we set up in A Default Command, on page 33. We could have specified the command directly in the docker-compose.yml file by setting a command option for web—this would have overridden the CMD instruction specified in the Dockerfile.

Go ahead and verify that our app is running: visit http://localhost:3000 in the browser. You should see the familiar Rails welcome page again.

Great! Our docker-compose.yml is working and everything is hunky-dory.

You can then terminate Compose by pressing Ctrl-C; you should see the containers being shut down.

Containers Not Shutting Down Gracefully



Unfortunately, Compose has an intermittent issue you'll need to watch out for. Occasionally, on terminating Compose with Ctrl-C, you may see ^CERROR: Aborting and find the containers aren't shut down. Unfortunately, if this happens, you'll have to stop the containers manually with docker-compose stop. See Chapter 9 for more details.

There's no need to run this now, but if we don't care about viewing the container output, we can start the containers in *detached* mode by specifying the -d option. This launches the application in the background and returns you to the shell prompt.