Linux Users: File Ownership



Make sure you have chowned the files by running:

```
$ sudo chown <your_user>:<your_group> -R .
```

See File Ownership and Permissions, on page 199, for more details.

```
$ docker-compose exec web bin/rails g controller welcome index
      create  app/controllers/welcome_controller.rb
       route  get 'welcome/index'
      invoke  erb
      create    app/views/welcome
      create    app/views/welcome/index.html.erb
      invoke  helper
      create    app/helpers/welcome_helper.rb
      invoke  assets
      invoke    coffee
      create      app/assets/javascripts/welcome.coffee
      invoke    scss
      create      app/assets/stylesheets/welcome.scss
```

Let's modify our welcome#index action (in app/controllers/welcome_controller.rb) to be as follows:

```
Line 1 class WelcomeController < ApplicationController
  2   def index
  3     redis = Redis.new(host: "redis", port: 6379)
  4     redis.incr "page hits"
  5
  6     @page_hits = redis.get "page hits"
  7   end
  8 end
```

In our index action, on line 3, we use the Redis client gem to connect to the Redis server by name and by the port number we expect it to be running on. Then, on line 4, we increment a Redis key-value pair, called "page hits." If you're wondering what happens the very first time this code is run, don't fret: if the key is not found, Redis will initialize it to zero, so our code will work as expected. Finally, on line 6, we fetch the current number of page hits from Redis, storing it in an instance variable, ready to display it in our view.

Now let's edit our view file (app/views/welcome/index.html.erb) to display the number of page hits:

```
<h1>This page has been viewed <%= pluralize(@page_hits, 'time') %>!</h1>
```

Finally, in config/routes.rb, let's change the autogenerated route so we can access our new WelcomeController's index action from /welcome (rather than /welcome/index):