கணிக்கீடு

HC for I set up = RL of A + BS of A 100.000 + 0.675 = 100.675

RL of B = HC for I set up – FS of B = 99.445

HC for II set up = RL of B + BS of B = 100.195

RL of C = HC for II set up – FS of C = 97.630

RL of D = HC for II set up - FS of D = 97.970

HC for III set up = RL of D + BS of D = 99.905

RL of E = HC for III set up – FS of E = 98.070

RL of F = HC for III set up – FS of F = 96.685

HC for IV set up = RL of F + BS of F = 99.880

RL of G = HC for IV set up – FS of G = 96.925

கணக்கீடுகளை சரிபார்த்தல்

Σ B.S ~ Σ F.S = first R.L ~ last R.L

6.475 ~ 9.550 = 100.000 ~ 96.925

3.075 = 3.075

நீருபிக்கப்பட்டது

(II) ஏற்ற இறக்க முறை

புள்ளி	BS	IS	FS	ஏற்றம் (+)	இறக்கம் (-)	RL	குறிப்புகள்
A	0.675					100.000	BM
B	0.750		1.230		0.555	99.445	CP_1
C		2.565			1.815	97.630	
D	1.935		2.225	0.340		97.970	CP_2
E		1.835		0.100		98.070	
F	3.115		3.220		1.385	96.685	CP_3
G			2.875	0.240		96.925	
Total	6.475		9.550	0.680			

கணிக்கீடு

புள்ளிகளுக்கு இடையே உள்ள மட்ட வேறுபாடு

A மற்றும் B புள்ளிகளுக்கு இடைப்பட்ட மட்ட வித்தியாசம் = 0.675 – 1.230 = - 0.555

B மற்றும் C புள்ளிகளுக்கு இடைப்பட்ட மட்ட வித்தியாசம் = 0.750 – 2.565 = - 1.815

C மற்றும் D புள்ளிகளுக்கு இடைப்பட்ட மட்ட வித்தியாசம் = 2.565 – 2.225 = - 1.960

D மற்றும் E புள்ளிகளுக்கு இடைப்பட்ட மட்ட வித்தியாசம் = 1.935 – 1.835 = + 0.100

E மற்றும் F புள்ளிகளுக்கு இடைப்பட்ட மட்ட வித்தியாசம் = 1.835 – 3.220 = - 1.285

F மற்றும் G புள்ளிகளுக்கு இடைப்பட்ட மட்ட வித்தியாசம் = 3.115 – 2.875 = +0.24

Civil_TAM_Unit-3.indd 61 1/11/2020 10:17:22 AM