Since there is no concurrent activity, skip the CONCURRENTLY keyword when building indexes. Autovacuum can also be disabled for this table. If the table was called trip_requests_intermediate then you'd run this SQL statement to disable Autovacuum:

sql/alter_table_disable_auto_vacuum.sql

```
ALTER TABLE trip_requests_intermediate
SET (autovacuum_enabled = false);
```

Next you'll put intermediate table techniques into practice with Rideshare.

Practicing Backfilling Techniques

Let's practice some of the backfill techniques to develop your skills in this area.

Using the example where you added a city_id column to the users table, imagine that you were creating a purpose-built intermediate table that would act as the data source to select from.

This table could have some of these characteristics:

- A minimal set of columns
- Purpose made index for a single query
- No constraints
- Unlogged
- Autovacuum disabled

Run these statements in psql:

```
CREATE SCHEMA IF NOT EXISTS temp;

CREATE UNLOGGED TABLE temp.users_intermediate (
  user_id bigint, city_id integer
);

ALTER TABLE temp.users_intermediate
SET (autovacuum_enabled = false);
```

Generate some rows:

```
INSERT INTO temp.users_intermediate (user_id, city_id)
SELECT GENERATE_SERIES(1, 10, 1), GENERATE_SERIES(1, 10, 1);
```

For your backfill, you'll UPDATE the users.city_id column, using matching rows from the temp.users table. If the users.city_id column does not exist, you can add it by running this statement in psql:

```
ALTER TABLE users ADD COLUMN IF NOT EXISTS city_id INTEGER;
```